

T-THATCH

LIQUID THATCH TREATMENT

APPLICATION OPTIONS

1. Standard thatch treatment

36L/Ha (standard rate)

48L/Ha (heavy thatch)

2. Annual OM treatment

Consume accumulated organic matter created by the growth cycle

36L/Ha

3. Scarifying and verti-cutting

Increase the amount of organic material removed by applying 10-14 days prior

36-48L/Ha

4. Intensive thatch program

Week 1: Scarify/verti-cut 3mm deep. Follow with Rocastem 10L/Ha and T-Thatch 36-48L/Ha

Week 3: Scarify/verti-cut to 3mm. Apply T-Thatch at 36-48L/Ha.

Week 5: Scarify/verti-cut 5-10mm deep.

☀️ Late-Spring to Autumn (minimum soil temperature 6°C). Repeat treatments as needed.

⚠️ For best performance in low pH soil conditions (below 5.4 pH) apply calcified seaweed at 2kg/100m². This will provide available calcium for microbe support.

Shelf life: 8 months. Once opened use within 28 days.

MIXING

- Recommended dilution rate 1:10+ litres water.
- T-Thatch is a two-part product requiring mixing of Part A and Part B.
- Add 10 litres of PART A and 2 litres of PART B to 120+ litres of water.
- Agitate before pouring, always pour concentrates into water volume.
- Compatible for tank mixing with all Terralift liquids.
- Ideal tank mix partner for Terralift Rocastem to boost aeration and recovery from thatch breakdown and removal.
- Complete spraying within 6 hours of mixing.
- Always water T-Thatch in to ensure it gets down into the thatch layer.

STORAGE

- Store in a cool, dry place out of direct sunlight. Do not allow to freeze. Part B is best kept between 2°C and 20°C.
- Product is not harmful to the environment when used in accordance with the label.
- Keep out of reach of children; May be harmful if swallowed; May cause irritation to eyes and skin.

FIRST AID

- Ingestion: drink plenty of water, seek medical aid.
- Eye or skin contact: wash thoroughly with water.

terralift.com.au  [terralift](https://www.facebook.com/terralift)  [terralift](https://twitter.com/terralift)  [terraliftfert](https://www.instagram.com/terraliftfert)

Terralift Australia, 11 North Wainwright Rd, Athol, QLD 4350, Australia

TERRALIFT

PERFORMANCE FERTILISERS

Made of more.

12L



T-THATCH

LIQUID THATCH TREATMENT

PART A

APPLICATION RATE

Standard rate: 36L/10,000m²

Heavy thatch rate: 48L/10,000m²

[10 litres PART A + 2 litres PART B]

MIXING

- Dilution rate 1:10+ litres water.
- Add 10L PART A and 2L PART B to 120+ litres of water.
- Agitate before pouring, always pour concentrate into the water volume.
- Complete spraying within 6 hours of mixing. Always water-in.
- Please refer to the carton and SDS for application and safety information.

TERRALIFT

PERFORMANCE FERTILISERS

Terralift Australia
11 North Wainwright Rd
Athol, QLD 4350, Australia

10L

T-THATCH

LIQUID THATCH TREATMENT

PART B

APPLICATION RATE

Standard rate: 36L/10,000m²

Heavy thatch rate: 48L/10,000m²

[10 litres PART A + 2 litres PART B]

MIXING

- Dilution rate 1:10+ litres water.
- Add 10L PART A and 2L PART B to 120+ litres of water.
- Agitate before pouring, always pour concentrate into the water volume.
- Complete spraying within 6 hours of mixing. Always water-in.
- Please refer to the carton and SDS for application and safety information.

TERRALIFT

PERFORMANCE FERTILISERS

Terralift Australia
11 North Wainwright Rd
Athol, QLD 4350, Australia

2L